



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS[®]

HEAT NO.:3116785 SECTION: FLAT 3/8X6 20'0" A36/52955 GRADE: ASTM A36-19/A529-14 Gr 55 ROLL DATE: 07/15/2022 MELT DATE: 07/13/2022 Cert. No.: 85157021 / 116785A046	S O L D T O	Supplier Supply & Steel Co	Delivery#: 85157021 BOL#: 74963558 CUST PO#: 235953-11 CUST P/N: DLVRY LBS / HEAT: 4590.000 LB DLVRY PCS / HEAT: 30 EA
---	--------------------------------	----------------------------	---

Characteristic Value		Characteristic Value		Characteristic Value	
C	0.10%	Elongation test 1	34%	The Following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
Mn	0.87%	Elongation Gage Lgth test 1	8IN		
P	0.013%	Yield to tensile ratio test1	0.79		
S	0.024%	Yield Strength test 2	57.1ksi		
Si	0.19%	Tensile Strength test 2	73.9ksi		
Cu	0.33%	Elongation test 2	33%		
Cr	0.12%	Elongation Gage Lgth test 2	8IN		
Ni	0.13%	Yield to tensile ratio test2	0.77		
Mo	0.031%				
V	0.015%				
Cb	0.016%				
Sn	0.010%				
B	0.0005%				
Ti	0.001%				
N	0.0084%				
Carbon Eq A6	0.31%				
Carbon Eq A529	0.34%				
Yield Strength test 1	57.6ksi				
Tensile Strength test 1	73.3ksi				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A529-55, A572-50, A572-55, A709-36, A709-50, AASHTO M270-36, M270-50, CSA G40.21-04 44W,50W, 55W