



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
830-372-8771

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila
Rolando A Davila
Quality Assurance Manager

1 SERIES-BPS[®]

HEAT NO.: 3091660
SECTION: ANG 2 X 2x3/16 20'0"
A36/52950
GRADE: ASTM A36-19/A529-14 Gr 50
ROLL DATE: 10/29/2019
MELT DATE: 10/05/2019
Cert. No.: 82940353 / 091660A111

S Superior Supply & Steel Co
O 318 N Cities Service Hwy
L Sulphur LA
D US 70663-5424
T 3376252300
O 3376258509

S Superior Supply
H 1948 Grand Caillou Rd
I Houma LA
P US 70363-7085
T 9852740111
O

Delivery#: 82940353
BOL#: 73355374
CUST PO#: PO212863-15
CUST P/N:
DLVRY LBS / HEAT: 4685.000 LB
DLVRY PCS / HEAT: 96 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.15%	Tensile Strength test 2	75.0ksi		
Mn	0.64%	Elongation test 2	28%		
P	0.012%	Elongation Gage Lgth test 2	8IN		
S	0.034%				
Si	0.18%				
Cu	0.30%				
Cr	0.13%				
Ni	0.10%				
Mo	0.036%				
V	0.000%				
Cb	0.009%				
Sn	0.009%				
Al	0.001%				
Carbon Eq A529	0.35%				
Yield Strength test 1	55.2ksi				
Tensile Strength test 1	75.1ksi				
Elongation test 1	29%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	54.7ksi				

The following is true of the material represented by this MTR:
 * Material is fully killed
 * 100% melted and rolled in the USA
 * EN10204:2004 3.1 compliant
 * Contains no weld repair
 * Contains no Mercury contamination
 * Manufactured in accordance with the latest version
 of the plant quality manual
 * Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
 * Warning: This product can expose you to chemicals which are
 known to the State of California to cause cancer, birth defects
 or other reproductive harm. For more information go
 to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W