



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUN TX 78155-7510

**CERTIFIED MILL TEST REPORT**  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Rolando A Davila  
Quality Assurance Manager

**1 SERIES-BPS** ®

HEAT NO.:3119956	S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85266532
SECTION: ANG 2 X 2x1/4 20'0" A36/52950	O	318 N Cities Service Hwy	H	318 N Cities Service Hwy	BOL#: 75130598
GRADE: ASTM A36-19/A529-14 Gr 50	L	Sulphur LA	I	Sulphur LA	CUST PO#: P0238166-11
ROLL DATE: 12/15/2022	D	US 70663-5424	P	US 70663-5424	CUST P/N:
MELT DATE: 11/27/2022	T	3376252300	T	3376252300	DLVRY LBS / HEAT: 18628.000 LB
Cert. No.: 85266532 / 119956A113	O	3376258509	O	3376258509	DLVRY PCS / HEAT: 292 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Tensile Strength test 2	75.1ksi	<p>The Following is true of the material represented by this MTR:</p> <ul style="list-style-type: none"> <li>*Material is fully killed and is Hot Rolled Steel</li> <li>*100% melted, rolled, and manufactured in the USA</li> <li>*EN10204:2004 3.1 compliant</li> <li>*Contains no weld repair</li> <li>*Contains no Mercury contamination</li> <li>*Manufactured in accordance with the latest version of the plant quality manual</li> <li>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</li> <li>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></li> </ul>	
Mn	0.99%	Elongation test 2	31%		
P	0.011%	Elongation Gage Lgth test 2	8IN		
S	0.033%				
Si	0.22%				
Cu	0.33%				
Cr	0.10%				
Ni	0.13%				
Mo	0.041%				
V	0.000%				
Carbon Eq A529	0.36%				
Yield Strength test 1	55.5ksi				
Tensile Strength test 1	74.9ksi				
Elongation test 1	30%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	56.0ksi				

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W