



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

**CERTIFIED MILL TEST REPORT**  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Drew M Fischer

**1SERIES-BPS**

Quality Assurance Manager

HEAT NO.: 3123509	S	Superior Supply & Steel Co	S	Superior Supply & Steel Co	Delivery#: 85465649
SECTION: ANG 2 X 2x3/8 20'0" A36/52950	O	318 N CITIES SERVICE HWY	H	318 N CITIES SERVICE HWY	BOL#: 75431593
GRADE: ASTM A36-19/A529-14 Gr 50	L	SULPHUR LA	I	US 70663-5424	CUST PO#: P0242044-01
ROLL DATE: 06/24/2023	D	US 70663-5424	P	3376252300	CUST P/N:
MELT DATE: 06/21/2023	T	3376252300	T	3376252300	DLVRY LBS / HEAT: 9400.000 LB
Cert. No.: 85465649 / 123509A713	O	3376258509	O	3376258509	DLVRY PCS / HEAT: 100 EA

Characteristic	Value	Characteristic	Value
C	0.11%	Tensile Strength test 2	75.4ksi
Mn	1.07%	Elongation test 2	30%
P	0.009%	Elongation Gage Lgth test 2	8IN
S	0.035%		
Si	0.23%		
Cu	0.31%		
Cr	0.08%		
Ni	0.14%		
Mo	0.041%		
V	0.000%		
Cb	0.014%		
Sn	0.009%		
Al	0.002%		
Carbon Eq A529	0.38%		
Yield Strength test 1	53.1ksi		
Tensile Strength test 1	75.6ksi		
Elongation test 1	27%		
Elongation Gage Lgth test 1	8IN		
Yield Strength test 2	52.9ksi		

The Following is true of the material represented by this MTR:

- \*Material is fully killed and is Hot Rolled Steel
- \*100% melted, rolled, and manufactured in the USA
- \*EN10204:2004 3.1 compliant
- \*Contains no weld repair
- \*Contains no Mercury contamination
- \*Manufactured in accordance with the latest version of the plant quality manual
- \*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
- \*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W