



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Drew M Fischer

1 SERIES-BPS[®]

Quality Assurance Manager

HEAT NO.: 3126285		S O		Superior Supply & Steel Co		S H		Superior Supply & Steel Co		Delivery #: 85595873	
SECTION: ANG 3 X 3x5/16 20"0"		L D		318 N CITIES SERVICE HWY		I P		318 N CITIES SERVICE HWY		BOL #: 75643753	
A36/52950		D		SULPHUR LA		P		SULPHUR LA		CUST PO#: P0245144-01	
GRADE: ASTM A36-19/A529-19 Gr 50		US		70663-5424		US		70663-5424		CUST P/N:	
ROLL DATE: 10/26/2023		T		3376252300		T		3376252300		DLVRY LBS / HEAT: 4636,000 LB	
MELT DATE: 10/17/2023		O		3376258509		O		3376258509		DLVRY PCS / HEAT: 38 EA	
Cert. No.: 85595873 / 126285A434											

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Yield to tensile ratio test 1	0.74		
Mn	0.88%	Yield Strength test 2	53.4ksi		
P	0.008%	Tensile Strength test 2	71.8ksi		
S	0.037%	Elongation test 2	33%		
Si	0.18%	Elongation Gage Lgth test 2	8IN		
Cu	0.35%	Yield to tensile ratio test 2	0.74		
Cr	0.10%				
Ni	0.11%				
Mn	0.041%				
V	0.000%				
Cb	0.012%				
Sn	0.012%				
Al	0.001%				
Carbon Eq A529	0.34%				
Carbon Eq A992	0.31%				
Yield Strength test 1	52.7ksi				
Tensile Strength test 1	71.2ksi				
Elongation test 1	34%				
Elongation Gage Lgth test 1	8IN				

The Following is true of the material represented by this MTR:
 * Material is fully killed and is Hot Rolled Steel
 * 100% melted, rolled, and manufactured in the USA
 * EN10204:2004 3.1 compliant
 * Contains no weld repair
 * Contains no Mercury contamination
 * Manufactured in accordance with the latest version of the plant quality manual
 * Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661
 * Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W