



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT

For additional copies call
830-372-8771

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

1SERIES-BPS®

HEAT NO.:3112028 SECTION: ANG 2 X 2x3/8 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50 ROLL DATE: 03/30/2022 MELT DATE: 01/11/2022 Cert. No.: 83811358 / 112028A713	S Superior Supply & Steel Co O L 318 N Cities Service Hwy D Sulphur LA US 70663-5424 T 3376252300 O 3376258509	S Superior Supply & Steel H I 318 City Service Highway P Sulphur LA US 70663-0000 T 3376252300 O 3376258509	Delivery#: 83811358 BOL#: 74703712 CUST PO#: 232465-11 CUST P/N: DLVRY LBS / HEAT: 9400.000 LB DLVRY PCS / HEAT: 100 EA
--	--	---	--

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Elongation test 2	31%		
Mn	1.00%	Elongation Gage Lgth test 2	8IN		
P	0.013%				
S	0.032%				
Si	0.20%				
Cu	0.33%				
Cr	0.07%				
Ni	0.12%				
Mo	0.030%				
V	0.000%				
Cb	0.012%				
Sn	0.011%				
Al	0.002%				
Carbon Eq A529	0.35%				
Yield Strength test 1	52.7ksi				
Tensile Strength test 1	73.6ksi				
Elongation test 1	28%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	53.1ksi				
Tensile Strength test 2	74.0ksi				
				<p>The Following is true of the material represented by this MTR:</p> <p>*Material is fully killed</p> <p>*100% melted and rolled in the USA</p> <p>*EN10204:2004 3.1 compliant</p> <p>*Contains no weld repair</p> <p>*Contains no Mercury contamination</p> <p>*Manufactured in accordance with the latest version of the plant quality manual</p> <p>*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661</p> <p>*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov</p>	

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W