



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUIN TX 78155-7510

**CERTIFIED MILL TEST REPORT**

For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

Rolando A Davila

Quality Assurance Manager

**1SERIES-BPS®**

HEAT NO.:3117532 SECTION: ANG 2 X 2x1/4 20'0" A36/52950 GRADE: ASTM A36-19/A529-14 Gr 50 ROLL DATE: 09/23/2022 MELT DATE: 08/13/2022 Cert. No.: 85217173 / 117532A113	S Superior Supply & Steel Co O L 318 N Cities Service Hwy D Sulphur LA US 70663-5424 T 3376252300 O 3376258509	S Superior Supply & Steel H I 318 City Service Highway P Sulphur LA US 70663-0000 T 3376252300 O 3376258509	Delivery#: 85217173 BOL#: 75055132 CUST PO#: P0237188-01 CUST P/N: DLVRY LBS / HEAT: 4657.000 LB DLVRY PCS / HEAT: 73 EA
--	--	---	---

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.11%	Elongation test 2	28%		
Mn	1.04%	Elongation Gage Lgth test 2	8IN		
P	0.012%				
S	0.044%				
Si	0.20%				
Cu	0.32%				
Cr	0.06%				
Ni	0.12%				
Mo	0.033%				
V	0.000%				
Cb	0.011%				
Sn	0.010%				
Al	0.000%				
Carbon Eq A529	0.37%				
Yield Strength test 1	56.4ksi				
Tensile Strength test 1	75.6ksi				
Elongation test 1	28%				
Elongation Gage Lgth test 1	8IN				
Yield Strength test 2	56.5ksi				
Tensile Strength test 2	75.6ksi				

**The Following is true of the material represented by this MTR:**  
*\*Material is fully killed and is Hot Rolled Steel*  
*\*100% melted, rolled, and manufactured in the USA*  
*\*EN10204:2004 3.1 compliant*  
*\*Contains no weld repair*  
*\*Contains no Mercury contamination*  
*\*Manufactured in accordance with the latest version of the plant quality manual*  
*\*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661*  
*\*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)*

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W