



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Drew M Fischer
Drew M Fischer

1 SERIES-BPS[®]

Quality Assurance Manager

HEAT NO.: 3121728
SECTION: ANG 2 1/2 X 2 1/2x1/4 20"0"
A36/52950
GRADE: ASTM A36-19/A529-19 Gr 50
ROLL DATE: 04/19/2023
MELT DATE: 04/07/2023
Cert. No.: 85529501 / 121728A397

S Superior Supply & Steel Co
O 318 N CITIES SERVICE HWY
L SULPHUR LA
D US 70663-5424
T 3376252300
O 3376258509

S Superior Supply & Steel Co
H 318 N CITIES SERVICE HWY
I SULPHUR LA
P US 70663-5424
T 3376252300
O 3376258509

Delivery#: 85529501
BOL#: 75533854
CUST PO#: P0243718-01
CUST P/N:
DLVRY LBS / HEAT: 4674,000 LB
DLVRY PCS / HEAT: 57 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Yield to tensile ratio test1	0.76		
Mn	1.07%	Yield Strength test 2	57.6ksi		
P	0.007%	Tensile Strength test 2	75.9ksi		
S	0.041%	Elongation test 2	31%		
Si	0.19%	Elongation Gage Lgth test 2	8IN		
Cu	0.32%	Yield to tensile ratio test2	0.76		
Cr	0.08%				
Ni	0.10%				
Mo	0.036%				
V	0.000%				
Cb	0.012%				
Sn	0.010%				
Al	0.001%				
Carbon Eq A529	0.36%				
Carbon Eq A992	0.33%				
Yield Strength test 1	57.9ksi				
Tensile Strength test 1	76.1ksi				
Elongation test 1	31%				
Elongation Gage Lgth test 1	8IN				

The Following is true of the material represented by this MTR:
 *Material is fully killed and is Hot Rolled Steel
 *100% melted, rolled, and manufactured in the USA
 *EN10204:2004 3.1 compliant
 *Contains no weld repair
 *Contains no Mercury contamination
 *Manufactured in accordance with the latest version of the plant quality manual
 *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 667
 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W