



CMC STEEL TEXAS  
1 STEEL MILL DRIVE  
SEGUN TX 78155-7510

CERTIFIED MILL TEST REPORT  
For additional copies call  
800-227-6489

We hereby certify that the test results presented here  
are accurate and conform to the reported grade specification

*Steve Fisher*

Draw M Fischer

Quality Assurance Manager

1 SERIES-BPS<sup>®</sup>

HEAT NO.: 3123840  
SECTION: CHANNEL 3"x4.1# 20"0"  
A36/52950  
GRADE: ASTM A36-19/A529-19 Gr50  
ROLL DATE: 10/06/2023  
MELT DATE: 07/05/2023  
Cert. No.: 85649815 / 123840A846

S O L D  
Superior Supply & Steel Co  
318 N CITIES SERVICE HWY  
SULPHUR LA  
US 70663-5424  
3376252300  
3376258509

S H I P  
Superior Supply & Steel Co  
318 N CITIES SERVICE HWY  
SULPHUR LA  
US 70663-5424  
3376252300  
3376258509

Delivery#: 85649815  
BOL#: 75728330  
CUST PO#: P0245785-01  
CUST P/N:  
DLVRY LBS / HEAT: 4674,000 LB  
DLVRY PCS / HEAT: 57 EA

Characteristic	Value	Characteristic	Value	Characteristic	Value
C	0.10%	Yield to tensile ratio test1	0.75		
Mn	1.00%	Yield Strength test 2	56.4Ksi		
P	0.010%	Tensile Strength test 2	74.8Ksi		
S	0.034%	Elongation test 2	32%		
Si	0.20%	Elongation Gage Lgth test 2	8IN		
Cu	0.31%	Yield to tensile ratio test2	0.75		
Cr	0.09%				
Ni	0.11%				
Mo	0.035%				
V	0.024%				
Cb	0.001%				
Sn	0.008%				
Al	0.000%				
N	0.0000%				
Carbon Eq A529	0.36%				
Yield Strength test 1	56.2Ksi				
Tensile Strength test 1	74.7Ksi				
Elongation test 1	32%				
Elongation Gage Lgth test 1	8IN				

The Following is true of the material represented by this MTR:  
 \*Material is fully killed and is Hot Rolled Steel  
 \*100% melted, rolled, and manufactured in the USA  
 \*EN10204:2004 3.1 compliant  
 \*Contains no weld repair  
 \*Contains no Mercury contamination  
 \*Manufactured in accordance with the latest version of the plant quality manual  
 \*Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661  
 \*Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W